

ENOC VERRON LX GREASE

PRODUCT DESCRIPTION

ENOC VERRON LX are high performance lithium complex greases with extreme pressure properties, developed for automotive wheel bearing lubrication where they can operate at high temperatures. They have excellent load carrying and anti-wear properties in both steel-on-steel and steel-on-bronze applications. They contain an effective oxidation and rust inhibitor and have low wash-out properties that are important performance requirements for wheel bearing lubrication.

APPLICATIONS

- ◆ Automotive vehicles
- ◆ Excellent high temperature control under severe breaking
- ◆ Suitable for heavily loaded bearings
- ◆ General mobile equipment
- ◆ Effective temperature range -15°C to 150°C

Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.

BENEFITS

VERRON LX provides:

- ◆ Excellent extreme pressure properties
- ◆ Resistance to water wash-out
- ◆ Suitability in high temperature applications
- ◆ Good pumpability
- ◆ Good mechanical stability

Technical Data*		
NLGI Grade	2	3
Dropping point, °C	260	260
Penetration, Worked @ 25°C	280	235
Color	Dark Blue	Dark Blue
Oil Viscosity		
mm ² /s @ 40°C	170	170
mm ² /s @ 100°C	16	16
Timken OK load, Kg	25	19
Operating temperature range °C	-15 to 150	-15 to 150
Product Code	224011	224012

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.